




Without LVGP

Ordering code	Voltage
LM()D * 24V AC	24V AC
LM()D * 48V AC	48V AC
LM()D * 110V AC	110V AC
LM()D * 220V AC	220V AC
LM()D * 415V AC	415V AC
LM()D * 12V DC	12V DC
LM()D * 24V DC	24V DC
LM()D * 48V DC	48V DC
LM()D * 110V DC	110V DC
LM()D * 220V DC	220V DC
LM()D * M	Multivoltage (24 to 220V AC/DC)



With LVGP (Low Voltage Glow Protection)

Ordering code	Voltage
LM()D * L 24V AC	24V AC
LM()D * L 48V AC	48V AC
LM()D * L 110V AC	110V AC
LM()D * L 220V AC	220V AC
LM()D * L 12V DC	12V DC
LM()D * L 24V DC	24V DC
LM()D * L 48V DC	48V DC
LM()D * L 110V DC	110V DC
LM()D * L 220V DC	220V DC



415V AC & Multivoltage LED module pilot lights do not have LVGP facility.

For Legend at * Refer Table Below

S. NO.	LEGEND
01	START
02	STOP
03	FWD
04	REV
05	UP
06	DOWN
07	ON
08	OFF
09	OPEN

S. NO.	LEGEND
10	CLOSE
11	AUTO
12	HAND
13	RESET
14	INCH
15	SLOW
16	FAST
17	PWR ON
18	E. STOP

S. NO.	LEGEND
19	RIGHT
20	LEFT
21	0
22	1
23	2
24	3
25	↑
26	L
27	R

S. NO.	LEGEND
28	Y
29	B
30	G
31	W
32	A
33	TRIP
34	SPRG. CHR.G.

() Colour Red - R
Amber - A
Green - G
Blue - B

Other legends also available on request.

All dimensions are in mm.
Due to continuous improvement in products, we reserve the right to alter specifications without prior notice